



DESIGNER:  
FU-TUNG CHENG  
LIMITED EDITION

MODEL	COK-E36BRGX	COK-E42BRGX	COK-E48BRGX
Rose Gold Stainless Steel	COK-E36BRGX	COK-E42BRGX	COK-E48BRGX
Black Mirror Stainless Steel	COK-E36BBMX	COK-E42BBMX	COK-E48BBMX
<b>Size</b>	36"	42"	48"
<b>Internal Blower CFM*</b>	290, CBI-290A	290, CBI-290A	290, CBI-290A
<b>Internal Blower CFM*</b>	600, CBI-600A	600, CBI-600A	600, CBI-600A
<b>In-line Blower CFM*</b>	1,000, PBN-1000A	1,000, PBN-1000A	1,000, PBN-1000A
<b>External Blower CFM*</b>	1,000, CBE-1000	1,000, CBE-1000	1,000, CBE-1000
<b>Sones</b>	1.4-6	1.4-6	1.4-6
<b>Controls</b>	Electronic Touch	Electronic Touch	Electronic Touch
<b>Speed Levels</b>	3	3	3
<b>Auto Delay-Off</b>	Yes	Yes	Yes
<b>CleanAir Function**</b>	Yes	Yes	Yes
<b>Lighting-Primary</b>	Bloom™ HD LED x2	Bloom™ HD LED x2	Bloom™ HD LED x4
<b>Lighting-Ambient</b>	Incandescent x2	Incandescent x2	Incandescent x2
<b>Dual-Level Lighting</b>	Yes, LED	Yes, LED	Yes, LED
<b>Filters</b>	Pro Baffle x1	Pro Baffle x1	Pro Baffle x2
<b>Wireless Remote Control</b>	Optional	Optional	Optional
<b>Recirculating</b>	No	No	No
<b>Duct Cover Extension</b>	No	No	No
<b>DUCT SPECIFICATIONS</b>			
<b>Vertical Internal</b>	6"	6"	6"
<b>Vertical In-Line/External</b>	10" to 8"***	10" to 8"***	10" to 8"***
<b>Horizontal</b>	NA	NA	NA
<b>AC INPUT</b>	120V - 60Hz	120V - 60Hz	120V - 60Hz
<b>AC POWER****</b>	Max. 0.6 Amps	Max. 0.6 Amps	Max. 0.7 Amps
<b>OPTIONAL ACCESSORIES</b>			
<b>Make-Up Air Kit</b>	MUA006A (600 CFM) MUA008A (1,000 CFM)	MUA006A (600 CFM) MUA008A (1,000 CFM)	MUA006A (600 CFM) MUA008A (1,000 CFM)
<b>Wireless Remote Control</b>	14000005	14000005	14000005
<b>MOUNTING HEIGHT RANGE†</b>	28" - 36"	28" - 36"	28" - 36"
<b>WARRANTY</b>	3 years parts, 1 year labor	3 years parts, 1 year labor	3 years parts, 1 year labor

CEILING HEIGHT	8'	8.5'	9'	9.5'	10'	10.5'	11'	12'
<b>MOUNTING HEIGHT†</b>	28" - 30"	26" - 34"	26" - 34"	28" - 36"	32" - 36"	NA	NA	NA

\*Blower sold separately.

\*\*CleanAir turns your hood on once every four hours for 10 minutes on speed one.

\*\*\*10" round duct connects to external and in-line blower. Must transition from 10" to 8" before duct passes through ceiling. A 10" to 8" adapter is included with external and in-line blowers.

\*\*\*\*AC power listed above is for hood with lights only. For blower specifications please refer to the blower spec sheet.

†Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.